

# COUNTERBALANCED STACKER TRUCKS

# BULLDOG

Capacity @ 500 L.C.	300 Kg		400 Kg		500 Kg			700 Kg	
Lift Height	1500	2100	1500	2100	1500	2100	2750	2100	2750
Closed Height	2055	1730	2055	1730	2055	1730	2055	1730	2055
Overall Raised Height	2095	2620	2095	2620	2095	2700	3350	2700	3350
Overall L x W	1733 x 780		1973 x 812		2131 x 952			2131 x 952	
Travel Speed-unloaded	5.3 K/hr		5.3 K/hr		5.3 K/hr			5.3 K/hr	
Maximum Gradient	9°/6°		9°/6°		9°/6°			9°/6°	
Gangway Width for 90° stacking 1000 x 1200mm pallet size	2133		2373		2531			2531	
Gangway Width for 90° stacking 1200 x 800mm pallet size	2333		2673		2731			2731	
Front Wheels	Ø200 Polyurethane		Ø200 Polyurethane		Ø200 Polyurethane			Ø200 Polyurethane	
Rear Wheels	Ø250 Polyurethane		Ø250 Polyurethane		Ø250 Polyurethane			Ø250 Polyurethane	
Mast Tilt	1/6°		1/6°		1/6°			1/6°	
Turning Radius	840/1170		900/1190		1190/1230			1190/1230	
Ground Clearance	58		58		58			58	
Battery	120 Ah Extra HD		100 to 219 Ah		100 to 219 Ah			100 to 219 Ah	
Weight	1050 Kg	1075 Kg	835 Kg	860 Kg	855 Kg	880 Kg	905 Kg	1150 Kg	1175 Kg
<b>Type</b>	<b>PDCB3 15 PDCB3 21</b>		<b>PDCB4 15 PDCB4 21</b>		<b>PDCB5 15 PDCB5 21 PDCB5 27</b>			<b>PDCB7 21 PDCB7 27</b>	

Lift heights 1.5m to 3.3m available



**A RANGE OF STACKER TRUCK ADAPTATIONS CAN BE SEEN ON PAGES 28 & 29**

**Optional Extras;** have been developed such as Side shift forks, Rider operated platforms, Duplex and Triplex lifts and flameproof versions for explosive atmospheres