

RIDER OPERATED TOW TRACTORS

ATLAS

Maximum Capacity	7000 Kg	10000 Kg	15000 Kg
Drawbar Pull (60 minute rating) (N)	1400	2000	3000
Height of Tow Hitch (from floor)	277/332mm	305/360mm	305/360mm
Unladen Weight (including batteries)	1235 Kg	2030 Kg	2320 Kg
Battery Weight	502 Kg	965 Kg	1210 Kg
Battery	270Ah 48v	360Ah 80v or 500Ah 80v	500Ah 80v
Drive Wheels	2 x Super Elastic	2 x Super Elastic	2 x Super Elastic
Drive Wheel	18x7-8	600-9	21x8-9
Max Par Pull (N)	4500	6500	8500
Front Wheel(s) Type	2 x Super Elastic	2 x Super Elastic	2 x Super Elastic
Front Wheels	4.00-4	400-8	16x6-8
Drive Motor(s)	2 x 2.5 Kw	2 x 4 Kw	2 x 5.5 Kw
Max Drive Speed Loaded/Unloaded	8/14Km/hr	11/18Km/hr	9/18Km/hr
Operational Brake	Hydraulic	Hydraulic	Hydraulic
Parking Brake	Manual	Manual	Manual
Overall Length	1730mm	2110mm	2110mm
Overall Width	970mm	1130mm	1130mm
Overall Height	1970mm	1990mm	1990mm
Wheel Base	1040mm	1360mm	1360mm
Ground Clearance	100mm	100mm	100mm
Turning Radius	1624mm	2200mm	2200mm
Max Gradient	See table below	See table below	See table below
Type	TA-7	TA-10	TA-15



Type TA-7

Optional Extras;
Fully fitted Rider
Cabs and Heavy
Duty Trailers

